

Application/Control Number: 10/774,921

Page 2

Art Unit: ***

CImpto

June 7, 2005

C.P.

Art Unit: ***

1. A solar light box comprising:
 - an upper step and a lower step, each step having a face and sides, the upper step substantially framing the lower step;
 - at least one light aperture in the lower step's face;
 - a light source mounted at least partially in the at least one light aperture;
 - a deep cavity in the lower step that is substantially defined by the lower step's face and sides;
 - a rain barrier ridge substantially around where an opening drops into the deep cavity;
 - at least one drainage passageway through the upper step; and
 - a solar panel substantially lying inside the upper step, between the upper step's sides.
2. The solar light box of claim 1 further comprising at least two slots that accept a mounting fork with ends; and a means for fastening the ends.
3. The solar light box of claim 1 further comprising a deep groove, substantially integral to the rain barrier ridge, that accepts a mounting hoop.
4. The solar light box of claim 1 further comprising: an energy-conserving switch; a sensor bracket, attached to the inside of the lower step; and a sensor aperture on the lower step's face such that the energy-conserving switch can be mounted partially inside the lower step.
5. The solar light box of claim 1 wherein the upper step's face contains at least as much surface area as the lower step's face.

Art Unit: ***

6. The solar light box of claim 1 further comprising a tamper-resistant means for securing the solar panel to the solar light box.

7. The solar light box of claim 1 further comprising small holes in the lower step for displaying light emitting diodes.

8. The solar light box of claim 1 further comprising a camera aperture for mounting a camera to the lower step.

9. An outdoor solar powered light assembly that uses a solar panel as a protective lid comprising:

a solar light box having an upper step and a lower step, each step having a face and sides, the upper step at least partially framing the lower step;

at least one aperture in the lower step's face for mounting a light source;

a deep cavity in the lower step that is substantially defined by the lower step's face and sides;

a rain barrier ridge, substantially around an opening to the lower step's deep cavity, that is formed where the lower step's sides extend above a plane defined by the upper step's face;

a rechargeable battery;

a solar panel, substantially lying between the upper step's sides, and covering the lower step's deep cavity;

a charge controller that is electrically connected between the solar panel and the rechargeable battery;

a sensor bracket attached to the inside of the lower step;

a sensor aperture through the lower step;

Art Unit: ***

an energy-conserving switch, electrically connected between the rechargeable battery and the light source, mounted to the sensor bracket and at least partially in the sensor aperture;

a means for securing the solar panel to the solar light box; and

a means for supporting the outdoor solar powered light assembly.

10. The outdoor solar powered light assembly of claim 9 wherein the light source is an array of white light emitting diodes.

11. The outdoor solar powered light assembly of claim 9 wherein the means for supporting the outdoor solar powered light assembly is a light pole mounted to the lower step of the solar light box.

12. The outdoor solar powered light assembly of claim 11 wherein the rechargeable battery is stored in a location that is remote from the solar light box, and wherein the rechargeable battery is electrically connected to the charge controller and the energy-conserving switch by wiring that at least partially passes through the interior of the light pole.

13. The outdoor solar powered light assembly of claim 9 wherein the rechargeable battery is stored in the deep cavity.

14. The outdoor solar powered light assembly of claim 9 wherein the means for securing the solar panel is at least one tamper-resistant fastener.

15. The outdoor solar powered light assembly of claim 9 further comprising at least one hinge for attaching a side of the solar panel to the solar light box such that the solar panel is capable of being lifted to expose the contents of the solar light box without completely removing the solar panel.

Art Unit: ***

16. The outdoor solar powered light assembly of claim 9 further comprising: a camera aperture in the lower step; and a camera mounted at least partially in the camera aperture.

Claims 17-20 cancelled

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: _____**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.